

CHICAGO 2 UNITS

MAIN FLOOR SCALE

1/4 = 1'-0"

DESIGN INFO

** TRUSS SPACING: 16"
** TRUSS DEPTH: 16"

** LOADING: TCLL - 40

BCLL - 0 TCDL - 10

BCDL - 5 TOTAL 55

			_
		Hanger Schedule	
Key	Model	Qty	
4	THA422	52	
			-

LVL - Girder hangers

BA3.56/16

HANGER FASTENER SPECS:

BA3.56/18 hanger fasteners (6) 10d top, (8) 10d face, (2) 10d x 1.5" supported

THA422 hanger fasteners (4) 16dx2.5" top, (2) 16dx2.5" face, (6) 10d supported

DATES: REVISIONS:

1.) REFER TO INDIVIDUAL TRUSS
..... DRAWINGS FOR ADDITIONAL INFO.
2.) DIMENSIONS SHOWN ARE FROM
..... FACE OF STUD OF BEARING WALLS
3.) DIMENSIONAL VERIFICATION IS THE

.....RESPONSIBILITY OF THE SITE
.....CONTRACTOR AND/OR ARCHITECT.
4.) ALL INTERIOR HEADERS TO BE
.....DROPPED EXCEPT AS NOTED.
5.) ALL TRUSSES MUST BE SPACED AT
.....A MAXIMUM OF 24" OC UNLESS
.....OTHERWISE NOTED.
6.) *DO NOT CUT, DRILL, OR ALTER

6.) *DO NOT CUT, DRILL, OR ALTER
.....*ANY TRUSS WITHOUT WRITTEN
.....*CONSENT FROM A REGISTERED
.....*ENGINEER.

These trusses are designed as individual building components to be incorporated into the building design at the specification of the Building Designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for: 1) Temporary and permanent bracing of the roof and floor system and for the overall structure; 2)The design of the entire truss support structure including but not limited to headers, beams, walls, and columns; 3)All truss-to-structure connections; 4) Verification of design criteria including loading and compliance with design documents; 5)Any other responsibilities as outlined in the governing codes and standards. For additional guidance see the latest adopted jurisdictional publications and/or visit

FLOOR PLAN

www.tpinst.org (USA) or www.tpic.ca (CANADA)

PROJECT
JOB NUMBER: XXXXXXX

JOB NOWBER. A

ING UNITS

VO DWELLING L TOWNHOME

CUSTOMER NAME: EZ 8

F-1

OF 1 SHEETS

ATE: 10/24/23